86-inch holographic digital transparent box

Model: WG-86S7

1. Product profile:

- Using IPS hard screen technology, large viewing Angle, fast response speed, high color reduction degree;
- Using 4K high-transmission display screen, the picture display is more perfect;
- 3840 * 2160 ultra-high resolution, the picture quality performance is more delicate;
- Panel protection using 5mm ultra-white crystal tempered glass hardness 6H;
- Using nano-capacitor touch, the operation is more convenient and perfect;
- 89 / 89 / 89 / 89 (Min.), (CR 10), which tends to approach the level;
- The whole metal structure, radiation, magnetic field, strong electric interference;
- Industrial-grade design, high reliability, high stability;

2. Product Appearance



3. Specification parameters:

Product reference figure / Product Reference Drawing		Size / size: 86 " inch Model number / model: WG-86S7
Panel parameters	Panel size / Panel size	86 " Inch
	Display area / Display Area	1895(H)X1065(V)mm
	Display mode / Display Mode	9:16
	LCD type / LCD Type	LCD glass / LCD panel
	Maximum resolution / Max Resolution	2160*3840
	Display the color / Display Color	16.7M
	Brightness / Bnightness	White 500 / 150 cd / m2 (center 1 point, typical value)
	Contrast ratio / Contrast	≥1000:1
	Visual Angle / Viewing Angle	89/89/89/89（Min.）(CR≥10)
	Response time / Response Time	8ms
	Refresh frequency / Field Frequency	60Hz
	Colour system / Color System	PAL/NTSC

	The Menu Language / OSD Language	Chinese, English / Chinese, English
Touch parameter / Touch parameters	Touch mode / Touch Style	Infrared touch / Infrared touch
	Touch points / Touch Style	20 points / 20 touch
	Touch the height	≤3mm
	Single point response time	≤12ms
	Touch positioning accuracy	±1mm
	Minimum touch object	≥2mm
Computer configuration / Computer Configuration	System / System	win
	CPU/CPU	i5 win 10
	internal storage /RAM	8G
	caliche /HD	256G RTX 3060
Camera camera / camera	4K camera and 4K camera	4K 500w pixel
Microphone / Microphone	8 Microphone array / 8 microphone arrays	8 microphone arrays, directional pickup echo elimination Intelligent noise reduction, far-field sound pickup The pickup distance reaches 10 meters 8 microphone arrays for directional pickup and echo cancellation Intelligent noise reduction and far-field pickup Pickup distance reaches 10 meters
Displays the drive card	4K UHD display drive board card	3840 x2160@60HZ
	output interface	Support for 2-channel HDMI 2.0 input

	Picture 10 / Picture	Support / BMP, JPEG, PNG, and GIF
Interface / Interface	HMDI	1
	Network port / Eternet	RJ45 10M/100M
	USB	2
Audio system / Audio Sytstem	Audio system / Audio Sytstem	Strong magnetic and high quality speaker body double speakers with co-shock Strong magnetic high-quality speaker with dual speakers and co vibration
	Sound standard	Full frequency sound
	Voice way	Middle and high notes before, bass after out
	The sound power	2×10W
	mega bass	support
source /Power	source /Power	AC100V~240V,50/60HZ
	Maximum power / Maximum Power	< 900W
	Standby power / standby power	< 1W
Working environment / work environment	Operating temperature is °C / Operating Temperature	0°C-50°C
Appearance / Figure	Case material / Frame material	Sheet metal / Hardware